Digital Tyre Inflator



XDA

Heavy Duty Inflator

The heavy duty, weatherproof and vandal resistant enclosure of the 89XDA makes it ideal for almost any indoor or outdoor location. These include: service centres, transport yards, military vehicle depots, mining sites, coach and bus depots, aircraft hangers and even retail petroleum forecourts.



89XDA-0026

Product Features

Accurate and easy to use with built in safety features

Rugged and attractive die-cast aluminium enclosure

Easy installation, 1m inlet hose & hook included

High reliability (vandal resistant) Piezo switches

Available in a range of standard corporate colours (high quality powder coat)

Nitrogen compatible

Technical Specifications	
Construction	Die Cast Aluminium Enclosure, IP66 rating
Dimensions	270W x 285H x 110D mm
Power Requirements	220~240VAC (optional 12VDC or 100~120VAC)
Unit of Measurement	psi / kPa / bar / kgcm²
Operating Range	5~145psi / 35~1000kPa / 0.3~10.0bar
Accuracy ±	± 0.3psi / 2kPa / 0.02bar

Included Accessories



61.0285 CRT Hose Assembly, 300mm, Mignon



61.0283 Hose Assembly, 300mm, Mignon



61.1308 Hose Kit, Black, Mignon, 8m



13.1407 Hose Hook, P/C White

1800 818 884 airtecaustralia.com.au tyre • pressure • mass